



ZhongRui Size Range

No.	Size(mm)		EP Tube(316L) Size Noted by ●
	O.D	Thk	
BA Tube Inner surface roughness Ra0.35			
1/4"	6.35	0.89	●
	6.35	1.00	●
3/8"	9.53	0.89	●
	9.53	1.00	
1/2"	12.70	0.89	
	12.70	1.00	
	12.70	1.24	●
3/4"	19.05	1.65	●
1	25.40	1.65	●
BA Tube Inner surface roughness Ra0.6			
1/8"	3.175	0.71	
1/4"	6.35	0.89	
3/8"	9.53	0.89	
	9.53	1.00	
	9.53	1.24	
	9.53	1.65	
	9.53	2.11	
	9.53	3.18	
1/2"	12.70	0.89	
	12.70	1.00	
	12.70	1.24	
	12.70	1.65	
	12.70	2.11	
5/8"	15.88	1.24	
	15.88	1.65	
3/4"	19.05	1.24	
	19.05	1.65	
	19.05	2.11	
1"	25.40	1.24	
	25.40	1.65	
	25.40	2.11	
1-1/4"	31.75	1.65	●
1-1/2"	38.10	1.65	●
2"	50.80	1.65	●
10A	17.30	1.20	●
15A	21.70	1.65	●
20A	27.20	1.65	●
25A	34.00	1.65	●
32A	42.70	1.65	●
40A	48.60	1.65	●
50A	60.50	1.65	

	8.00	1.00	
	8.00	1.50	
	10.00	1.00	
	10.00	1.50	
	10.00	2.00	
	12.00	1.00	
	12.00	1.50	
	12.00	2.00	
	14.00	1.00	
	14.00	1.50	
	14.00	2.00	
	15.00	1.00	
	15.00	1.50	
	15.00	2.00	
	16.00	1.00	
	16.00	1.50	
	16.00	2.00	
	18.00	1.00	
	18.00	1.50	
	18.00	2.00	
	19.00	1.50	
	19.00	2.00	
	20.00	1.50	
	20.00	2.00	
	22.00	1.50	
	22.00	2.00	
	25.00	2.00	
	28.00	1.50	
BA Tube , No request about the inner surface roughness			
1/4"	6.35	0.89	
	6.35	1.24	
	6.35	1.65	
3/8"	9.53	0.89	
	9.53	1.24	
	9.53	1.65	
1/2"	12.70	0.89	
	12.70	1.24	
	12.70	1.65	
	6.00	1.00	
	8.00	1.00	
	10.00	1.00	
	12.00	1.00	
	12.00	1.50	



ISO9001/2015 Standard



ISO 45001/2018 Standard



PED Certificate



TUV Hydrogen compatibility test certificate